

Reliability Analysis of k-out-of-n: G System: A Short Review

Ragi Krishnan

Abstract— Reliability analysis of k-out-of-n: G system have seen a tremendous growth in the last few decades. This paper presents an overview of the research on reliability studies of k-out-of-n: G systems. Methods for reliability evaluation, lifetime distributions of failure rate of components and systems with different types of components are presented.

Index Terms — reliability, k-out-of-n: G systems, availability, MTTF

I. INTRODUCTION

The k-out-of-n system structure is a very popular type of redundancy in fault tolerant systems with wide applications both in industrial and military systems. Fault-tolerant systems include the multi display system in a cockpit, the multiengine system in an airplane and the multi pump system in a hydraulic control system. In a data processing system with five video displays, a minimum of three displays operable may be sufficient for full data display. In this case, the display subsystem behaves as a 3-out-of-5: G system. Systems with spares may also be represented by the k-out-of-n system model. In k-out-of-n systems, system consists of n components, in which k of the n components must be good for the system to operate ($k < n$). A bridge with n cables, where a minimum of k cables are necessary to support the bridge is an example of k-out-of-n system. In k-out-of-n system, when an operating component fails, a standby component gets replaced automatically. The special case $k=n$ corresponds to the series system while $k=1$ corresponds to the parallel system. A system of n components works (or is “good”) if and only if at least k of the “n” components work (or are “good”) is called a k-out-of-n: G system.

The analysis of reliability models have been a subject of interest for the last few decades. Rau [27] in his book has made a fine analysis on the basics of reliability. He derived the reliability of many systems has given the results for reliability of standby systems, (m,n) systems with repair, systems with spares, reliability allocation, repair as renewal process, Markov techniques etc. For a repairable k-out-of-n system, it fails only if the total number of failed components at any instant of time reaches $n-k+1$. Assume that all of the system’s components are working at time zero. Thus, the system is in the up state at time zero. As components fail, repair work is performed on the failed components. If the number of failed components in the failed state reaches the state $n-k+1$, the system makes a transition from the up state to the down state. When the system is down, repair work continues on the failed components and the system will return to the up state as soon as the number of failed components becomes lower than $n-k+1$. It is obvious that the behavior of the system constitutes a delayed alternating renewal process. Ramakumar [59] in his book, “Engineering reliability: Fundamentals and Applications” has given the basics of

reliability and basic properties used in the analysis of reliability. Lam [42] calculated the rate of occurrence of failures for continuous-time Markov chains with application to a two-component parallel system.

1. Reliability of k-out-of-n system

She and Pecht [65] studied reliability of a k-out-of-n: warm standby system. Joseph and Manoharan [28] had given an explicit solution of a Markovian k-out-of-n system. In that paper the transient probabilities and steady state probabilities are obtained using Markov model formulation and Matrix method. Jinsheng Huang studied a generalized multi-state k-out-of-n:G Systems. Huamin Liu [25] had given his discoveries on the reliability of a load sharing k-out-of-n: G system: Non i.i.d. components with arbitrary distributions. Kuo and Zuo [38,39] presented a comprehensive review of research work on repairable k-out-of-n system models with independent and identical components. The optimal design of k-out-of-n:G subsystems subjected to imperfect fault-Coverage have given by Suprasad V. Amari[72]. Xiahu Li et al [78] derived the reliability of a repairable k-out-of-n system with some components being suspended when the system is down. Srinivas R. Chakravarthy [70] had given his research on the influence of delivery times on repairable k-out-of-N systems with spares.

2. Reliability and cost analysis of k-out-of-n system

Cost effectiveness is a measure of the combined effects of system cost and system effectiveness. Some work has been done on the optimal operating policy for a queuing system with linear cost structure. So many authors have solved queuing problems with additional service facility. The queuing system with additional service channel was studied by Philips [54], Murari [47], Bindhi Singh [6] and Arulmozhi [4]. Cost analysis of two unit system is done by Parthasarathy [50]. The cost models applied to reliability have been considered by Goel et al [19]. The cost analysis of a two-unit repairable system subject to online preventive maintenance and/or repair is discussed by Gopalan et al [20]. M/M/R machine repair problem with warm standbys under steady state conditions is studied by Wang [76]. A profit model in order to determine the optimal value of number of spares and the number of repairmen simultaneously have been developed by them. K-out-of-n:G system with cost considerations is studied by Ronold [61]. The economic analysis of (M, N) reliability model with threshold value was analyzed by Arulmozhi [3]. As proposed by this model, if the number of failed lines exceed some number say M where $M < (n-k+1)$, the automated additional sensor comes online and

additional service facility is introduced. This will maintain the required minimum lines.

3. Consecutive k-out-of-n system

A consecutive- k-out-of-n: F system ($C(k,n:F)$ system) consists of a sequence of ordered components along a line or a circle such that the system is failed if and only if at least k consecutive components in the system are failed. It has been first introduced by Kontoleon [32]. Antonopoulou et al [2] derived a fast recursive algorithm to evaluate the reliability of a circular consecutive-k-out-of-n: F system. Kuo et al [39] had studied the relation between consecutive-k-out-of-n: G system and consecutive -k-out-of-n: F system and presented in his paper "A consecutive- k-out-of-n: G system: The mirror image of consecutive-k-out-of-n: F system". To improve the availability of the system, Zhang et al [85] introduced the concept of key components and adopted a more reasonable queuing discipline for repair, which assigns a higher priority to key components. They analyzed a repairable circular consecutive-2-out-of-n system with priority in repair. Also, the exact reliability formula for consecutive-k-out-of-n repairable system is derived by Liang et al [79]. However, in all these research works, the authors considered only the system with one repairman. Recently, Yueqin Wu and Jiancheng Guan [83] analyzed repairable linear or circular systems with r repairmen and provided a general formula to calculate M_{-i} , the number of different cases when the system is in state-i. The state -i indicates that the system is working with i failed components in total.

4. k-out-of-n system with fault coverage

In all studies on k-out-of-n systems, the reliability and availability analysis is based on the failure rate and repair rate of the system. But the failure of a component may be covered or uncovered. In practical the failures of the system may not be covered always because of the non availability of repairmen in repair facility. Shakil Akhtar [64] studied reliability of k-out-of-n system with imperfect fault coverage. In his paper both possibilities of a k-out-of-n model with sensor in which all the failure can be repaired and another model in which the failures can lead to an absorbing state in which there is no transmission is possible to a functional state is discussed. Krishnamoorthy et al [33,34,35] studied k-out-of- n:G systems with various repair various repair policies. Hoanpham [24] has presented a handbook on reliability engineering. Optimal design of k-out-of-n: G subsystems subjected to imperfect fault coverage is given by Suprasad Amari [72]. Yamamoto et al [23] given some recursive formulas for the reliability of multi state consecutive-k-out-of-n: G systems. Transient analysis reliability with and without repair for k-out-of-n: G systems with two failure modes is done by Moustafa [45].

5. k-out-of-n system with different types of components

Habib et al [22] presented a newly developed model; consecutive-(r,s)-out-of-(m,n):F lattice system. The reliability of systems with imperfect sensing and switching was studied

by so many authors (Prakash [52], Nakagawa and Osaki [48], Kececiogulu and Jian [30], Mustafa [1], Chow [10]. The mean residual life functions of parallel and k-out-of-n:G system with non-identical components is studied by Selma Gurlur [62]. Various systems and their reliability parameters are given explicitly in the book of Srinath [69]. Reliability of some redundant systems with repair is given by Chow [11]. The reliability of incomplete k-out-of-n:G systems is analyzed by Behr [5] and formulas for computing the reliability is given by the author. Kullstam [37] have given availability, MTBF and MTTR of repairable m -out-of-n system. Xiaohu Li et al [78] analyzed the reliability of a repairable k-out-of-n system with some components being suspended when the system is down. Recently, Zhang et al [84] studied the general availability and reliability of k-out-of-(M+N): G warm standby system. In this, the system is composed of two types of components Type-I and Type-II. Components of Type-I have lower failure rate and are preferably repaired. Several repair facilities are considered. Khatab et al [31] have studied the availability of k-out-of-n: G systems with non-identical components subject to repair priorities. In this paper, a k-out-of-n: G system with N categories of components is studied. Each component category is characterized by its own failure and repair rates.

6. Conclusion

In this review article we have discussed k-out-of-n systems with various cases. There are many real time applications for k-out-of-n systems. For example, a four-engine aircraft needs only two engines to perform critical function; the operating and standby engine may fail in different modes with different rates. Communication systems with three transmitters having different types of failures; the average message load may be such that at least two transmitters must be operational at all times otherwise critical message will be lost. Here we have discussed only some works on k-out-of-n systems. These can be further extended for models with unreliable repairman and optimal number of standby machines or repairmen.

REFERENCES

- [1] Alidrisi Mustafa, M. "The Reliability of a dynamic warm standby redundant system of n-components with imperfect switching", Micro electron Reliability, Vol. 32, No.6, pp.851-859, 1992.
- [2] Antonopoulou, I and Papastavridis, S. "Fast recursive algorithm to evaluate the reliability of a circular consecutive-k-out-of-n: F system", IEEE Transaction on Reliability, Vol. 36, pp. 83-84, 1987.
- [3] Arulmozhi, G. "Direct method for reliability computation of k-out-of-n: G systems", Applied Mathematics and Computation, pp.421-429, 2003.
- [4] Arulmozhi, G. "Economic Analysis of (M, N) Reliability Model with threshold value", Proceedings of the International Conference on Stochastic models, Optimization Techniques and Computer Applications, Wiley Eastern Limited, pp. 178-191, 1994.
- [5] Behr, A. and Camarinopoulos, L. "Two formulas for computing the reliability of incomplete k-out-of-n: G systems", IEEE Transactions on Reliability, Vol. 46, No.3, pp. 421-429, 1997.
- [6] Bindhi Singh, K. "Cost analysis of a queuing system with two server facilities", Journal of Operations Research, Vol. 22, pp. 67-76, 1988.
- [7] Chao, M.T. and Lin, G. D. "Economical design of large consecutive k-out-of-n: F system", IEEE Transaction on Reliability, R-33 (1), pp. 411-413, 1984.

- [8] Cheng, K. and Zhang, Y. L. "Analysis for a consecutive-k-out-of-n: F repairable system with priority in repair", *International Journal of System Science*, Vol. 32, pp. 591–598, 2001.
- [9] Chiang, D.T. and Niu, S. C. "Reliability of a consecutive-k-out-of-n: F system", *IEEE Transaction on Reliability*, Vol. 30, pp. 87–89, 1981.
- [10] Chow, D.K. "Reliability of some redundant system with repair", *IEEE Transactions on Reliability*, Vol.R-22, No.4, pp. 223-228, 1973.
- [11] Chow, D. K. "Reliability of two items in sequence with sensing and switching", *IEEE Transaction on Reliability*, R-20, pp.254-256, 1971.
- [12] Cox, D. R. *Renewal Theory*, Methuen and Co. Ltd, London, 1962.
- [13] Daniel Beaudry, M. "Performance related reliability measures for computing systems", *IEEE Transactions on Computers*, Vol. C-27, pp.540-547, June 1978.
- [14] Derman, C., Lieberman, G. J. and Ross, S. M. "On the consecutive-k -out-of-n: F system", *IEEE Transaction on Reliability*, Vol. 31, pp. 57–63, 1982.
- [15] Dhillon, B.S. and Singh, C. *Engineering reliability-New Techniques and Applications*, New York, John Wiley- Inter science, 1981.
- [16] El-Damcese, M. "An Analysis of Warm Standby Systems Subject to Common Cause Failures with Time Varying Failure and Repair Rates", *Applied Mathematical Sciences*, Vol. 3, No. 18, pp. 853 – 860, 2009.
- [17] Fu, J. C. "Reliability of a Large Consecutive-k-out-of-n: F system", *IEEE Transactions on Reliability*, Vol. 34, pp. 127–130, 1985.
- [18] Gera, A. E. "A consecutive-k-out-of-n: G system with dependent elements - A matrix formulation and solution", *Reliability Engineering and System Safety*, Vol.68, pp. 61–67, 2000.
- [19] Goel, L. R., Gupta, R. and Singh, S. K. "Cost analysis of a two unit cold standby system with two types of operation and repair", *Microelectron Reliability*, Vol.25, No.1, pp.71-75, 1985.
- [20] Gopalan, M. N. and Bhanic, K.S. and Muralidhar, N. "Cost analysis of a two unit repairable system subject to online preventive maintenance and/ or repair", *Micro Electron Reliability*, Vol. 32, No.12, pp. 1675-1679, 1992.
- [21] Gopalan, M. N. "Probabilistic analysis of a single server N- unit system with N-1 standbys", *Journal of Operations Research*, Vol. 23, pp.591-595, 1975.
- [22] Habib, A. S., Yuge, T., Al-Seedy, R.O. and Ammar, S.I. "Reliability of a consecutive (r,s)-out-of-(m,n) : F lattice system with conditions on the number of failed components in the system", *Applied Mathematical Modeling* ,Vol.34, No. 3, pp.531-538, 2009.
- [23] Hisashi Yamamoto, Ming, J. and Zuo. "Recursive formulas for the reliability of multi-state consecutive-k-out-of-n: G systems", *IEEE Transactions on Reliability*, Vol.55, No.1, pp. 98-104, [].
- [24] Hoanpham, Ph.D., *Handbook of Reliability Engineering*, Springer-Verlag London Ltd., 2003.
- [25] Huamin Liu. "Reliability of load sharing k-out-of-n: G system: Non-iid components with arbitrary distributions", *IEEE Transactions on Reliability*, Vol. 47, No.3, pp. 279-284, 1998.
- [26] James, C. Fu. "Reliability of consecutive-k-out-of-n: F Systems with (k-1)-step Markov dependence", *IEEE Transactions on Reliability*, Vol.R-35, No.5, pp.602-606, 1986.
- [27] John, G. Rau. *Optimization and Probability in systems Engineering*, Van Nostrand Reinhold Company, 1970.
- [28] Joseph, K. X. and Manoharan, M. "Explicit solutions of a Markovian k-out-of-n systems", *Statistical Methods in Quality and Reliability*, Educational Publishers and Distributers, pp. 122-128, 1998.
- [29] Kececioğlu, D. *Reliability Engineering Handbook*, Prentice, Engle wood Cliffs. N J, 1992.
- [30] Kececioğlu, D. and Jiang, S. "Reliability of repairable standby system with imperfect sensing and switching", *Proceedings 1990 Annual Reliability and Maintainability Symposium*, pp. 261-267, 1990.
- [31] Khatib, A., Nahas, N. and Nourelfath, M. "Availability of K-out-of-N: G systems with non-identical components subject to repair priorities", *Reliability Engineering and System Safety*, Vol.94 (2), pp.142-151, 2009.
- [32] Kontoleon, J. M. "Reliability determination of a r-successive-out-of-n. F system", *IEEE Transactions on Reliability*, R-29(5), pp.437, 1980.
- [33] Kontoleon, J. M. "Analysis of a dynamic redundant system with non identical units", *IEEE Transactions on Reliability*, R-29(1), pp.77–78, 1980.
- [34] Krishnamoorthy, A. and Ushakumari, P. V. and Lakshmi, "K-out-of-n system with repair; the N-policy", *Asia Pacific Journal of Operation Research*, Vol.19, pp. 47-61, 2002.
- [35] Krishnamoorthy, A. and Ushakumari, P. V. and Lakshmi, "K-out-of-n: G system with repair; the D-policy", *Computers and Operation Research*, Vol. 28, pp. 973-981, 2001.
- [36] Krishnamoorthy, A. and Rekha, A. "K-out-of-n system with repair: T-policy", *Korean Journal of computers and Applied Mathematics*, Vol.8, No.1, pp.199-212, 2001.
- [37] Kullstam, P.A. "Availability, MTBF and MTTR for repairable m-out-of-n system", *IEEE Transactions on Reliability*, Vol. R-30, pp. 393-394, 1981.
- [38] Kuo, W. and Zuo, M. J. *Optimal Reliability Modeling, Principles and Applications*, John Wiley & Sons, New York, 2003.
- [39] Kuo, W. Zhang, W. X. and Zuo, M. J. "A consecutive-k-out-of-n: G system: The mirror image of a consecutive-k-out-of-n: F system", *IEEE Transactions on Reliability*, Vol. 39, pp. 244–253, 1990.
- [40] Lam, Y. "The rate of occurrence of failures", *Journal of Applied Probability*, Vol. 34, pp. 234-247, 1997.
- [41] Lam, Y. "A repair replacement model", *Advanced Applied Probability*, Vol.22, pp. 94-97, 1990.
- [42] Lam, Y. "Calculating the rate of occurrence of failures for continuous-time Markov chains with application to a two-component parallel system", *Journal of Operational Research Society*, Vol. 46, pp. 528-36, 1995.
- [43] Lam, Y. and Zhang, Y. L. "Repairable consecutive-k-out-of-n: F system with Markov dependence", *Naval Research Logistics*, Vol. 47, pp. 18–39, 2000.
- [44] Lam, Y and Zhang, Y. L. "Repairable consecutive-k-out-of-n: G system", *Chinese or Transactions*, Vol. 4, pp. 19–32, 2000.
- [45] Magdi, S. Mustafa. "Transient analysis of reliability with and without repair for k-out-of-n: G system with M failure modes", *Reliability Engineering and System Safety*, Vol. 53, Issue-1, pp. 31–35, July 1996.
- [46] Majid Asadi. and Ismihan Bayramoglu. "The Mean residual life function of a k-out-of-n structure at the system level", *IEEE Transactions on reliability*, Vol. 55, No.2, pp. 314-318, 2006.
- [47] Murari, K. and Vibha Goyal. "Cost Analysis of a two unit warm standby reliability system with two types of repair facilities", *Micro electron Reliability*, Vol.25, No.4, pp. 681-689, 1985.
- [48] Nakagawa, T. and Osaki, T. "Stochastic of two unit standby redundant systems with imperfect switchover", *IEEE Transaction on Reliability*, R-24, pp. 143-146, 1975.
- [49] Offer Keller. "The threshold policy in the M/G/1 queue with server vacations", *Naval Research Logistics*, Vol. 3, pp. 111-123, 1989.
- [50] Parthasarathy, P.R. "Cost analysis for two-unit systems", *IEEE Transactions on Reliability*, R-28, pp.268-269, 1979.
- [51] Par, S. Tenbohlen, T. and Stirl, M. Rosner. "Benefit of sensors for online monitoring systems for power transformers", *Online monitoring of internet, Online monitoring of power Transformers*, pp.1-5, 2003.
- [52] Prakash, S. "Some reliability characteristics of standby redundant equipment with imperfect switching", *Microelectron Reliability*, Vol.9, pp. 419-423, 1970.
- [53] Papastavridis, S. G. "The most important component in a consecutive-k-out- of-n: F system", *IEEE Transactions on Reliability*, Vol. 36, pp. 266–268, 1987.
- [54] Philips, C. R. "A variable channel queuing model with limited number of channels", Thesis, Georgia Institute of Technology, 1960.
- [55] Prabha, N. and Chandrasekhar, P. "Reliability analysis of a complex two unit standby system with Erlangian repair time", *Statistical methods*, Vol. 4 (2), pp. 113-121, 2002.
- [56] Ragi Krishnan, Somasundaram, S. "The Survival Analysis of k-out-of-n system", *International Journal of Statistics and Systems*, Vol. 4, No.1, pp. 25-32, 2009.
- [57] Ragi Krishnan, Somasundaram, S. "The reliability analysis of k-out-of-n:G repairable system with sensor and r repairmen",

- International Journal of Quality and Reliability Management, Vol. 28, No.8 and 9, pp. 894-908 with Impact Factor 0.34 , 2011.
- [58] Ragi Krishnan, Somasundaram, S. "The Reliability and Profit Analysis of k-out-of-n: G systems with Sensor", European Journal of Scientific Research, Vol. 67, No.2 pp.215-222 with Impact Factor 0.02, January 2012.
- [59] Ramakumar, R. Engineering Reliability Fundamentals and Applications, Prentice Hall, New Jersey, 1993.
- [60] Ross, S.M. Applied probability models with optimization applications, Holden-Day, San Francisco, 1970.
- [61] Ronald, C. Suich, Richard, L. Patterson. "K-out-of-n: G Systems: Some Cost Considerations", IEEE Transactions on Reliability, Vol. 40, No. 3, pp.259- 264, 1991.
- [62] Selma Gurler., Ismihan Bairamov. "Parallel and k-out-of-n: G systems with non identical components and their mean residual life functions", Applied Mathematical Modeling, Vol.33, pp. 1116-1125, 2009.
- [63] Serkan Eryilmaz. "Reliability properties of consecutive k-out-of-n systems of arbitrarily dependent components", Reliability Engineering and System Safety, Vol. 94, pp.350-356, 2009.
- [64] Shakil Akhtar. "Reliability of k-out-of-n: G systems with imperfect fault coverage", IEEE Transactions on Reliability, Vol. 43, No. 1, pp.101-106, 1994.
- [65] She, J. and Pecht, M.G. "Reliability of a k-out-of-n Warm-Standby System", IEEE Transactions on Reliability, Vol.41, No.1, pp. 72-75, 1992.
- [66] Shooman, M.L. Probabilistic Reliability, An Engineering Approach, Mc. Graw-Hill Book Co., New York, 1968.
- [67] Singh, J. "A warm standby redundant systems with common cause failures", Reliability Engineering and System Safety, Vol. 26(2), pp.135-41, 1989.
- [68] Somasundaram, S. "Analysis of system reliability with stress, strength and switching", Ph.D Thesis, Bharathiar University, Coimbatore, India (1999).
- [69] Srinath, L.S. Reliability Engineering, Third edition, Affiliated East-West Press Pvt. Ltd., New Delhi, 1991.
- [70] Srinivas, R. Chakravarthy. and Gómez-Corral, A. "The influence of delivery times on repairable k-out-of-N systems with spares", Applied Mathematical Modeling, Vol.33 (5), pp.2368-2387, 2009.
- [71] Stavros, G. Papastavridis. and Markos, V. Koutras. "Bounds For Reliability of Consecutive k-within-m-out-of-N: F Systems", IEEE Transactions on Reliability, Vol. 42, No. 1, pp. 156-161,1993.
- [72] Suprasad, V. Amari. "Optimal design of k-out of-n: G Subsystems subjected to imperfect fault coverage", IEEE Transactions on Reliability, Vol.53, No.4, pp. 567-575, 2004.
- [73] Suprasad, V. Amari. "Generic rules to evaluate system-failure frequency", IEEE Transactions on Reliability, Vol.49, No. 1, pp. 85-87, 2000.
- [74] Suprasad, V. Amari. "Bounds on MTBF of systems subjected to periodic maintenance", IEEE Transactions on Reliability, Vol.55, No.3, pp. 469-474, 2006.
- [75] Ushakumari, P. V. and Krishnamoorthy, A. "K-out-of-n system with repair: the max (N,T) policy", Performance Evaluation An International Journal , Vol. 57, pp. 221-234,2004.
- [76] Wang, K.H. and Sivazlian, B.D. "Reliability of a system with warm standbys and repairmen", Microelectron Reliability, Vol.29, No.5, pp.849-860, 1989.
- [77] Wu, Y. Q. and Guan, J.C. "Reliability of consecutive-k-out-of-n : G systems with r repairmen", IEEE Transactions on Reliability, Vol. 54, No 2, pp. 328-337, 2005.
- [78] Xiaohu Li, Ming, J.Zuo. and Richard, C. M. Yam. "Reliability analysis of a repairable k-out-of-n system with some components being suspended when the system is down", Reliability Engineering and System Safety, Vol. 91, pp.305-310, 2006.
- [79] Xiaolin Liang, Y. Xiong and Zehui Li. "Exact reliability formula for consecutive k-out-of-n repairable systems", IEEE Transactions on Reliability, Vol. 59, No.2, pp. 313-318, 2010.
- [80] Yam, R.C.M., Zuo, M. J. and Zhang, Y. L. "A method for evaluation of reliability indices for repairable circular consecutive-k-out-of-n: F systems", Reliability Engineering and System Safety, Vol. 79, pp. 1-9, 2003.
- [81] Yonit Barron, Esther Frostig and Benny Levikson. "Analysis of R-out-of- N systems with several repairmen, exponential life times and phase type repair times: An algorithmic approach", European Journal of Operational Research, Vol. 169, pp. 202-225, 2006.
- [82] Young, D. N. and Gregory, R. T. A Survey of Numerical Mathematics, Addison Wesley Englewood Cliffs, NJ, 1973.
- [83] Yueqin, Wu. and Jiancheng, Guan. "Repairable Consecutive-k-out-of-n:G systems with R repairmen", IEEE Transactions on Reliability, Vol. 54, No.2, pp. 328-337, June 2005.
- [84] Zhang, T., Min, Xie. and Michio, Horigome. "Availability and Reliability of k-out-of-(M+N): G warm standby systems", Reliability Engineering and System Safety, Vol. 91, pp. 381-387, 2006.
- [85] Zhang, Y. L. and Y. Lam, "Reliability of consecutive-k-out-of-n: G repairable system", International Journal of System Science, Vol. 29, pp. 1375-1379, 1998.

Dr. RAGI KRISHNAN received her B.Sc and M.Sc. degree in Mathematics from University of Calicut, Kerala, India. She completed her M.Phil degree in Mathematics from Annamalai University, Tamil Nadu, India in 2006. She received her Doctorate in Philosophy in Mathematics from Anna University, Chennai India in 2013. She has more than 14 years of experience in teaching Mathematics for various engineering colleges. She has been serving as a faculty member in the Department of Mathematics, PSG College of Technology, India since 2014. Her research interest includes Reliability and Graph theory. She has four paper publications in various National and International Journals.